

SHEET ALIGNING APPARATUS

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to a sheet aligning apparatus in a sheet feeding apparatus.

Related Background Art

 In conventional image reading apparatuses provided in copying machines, facsimile apparatuses, and the like, a sheet feeding apparatus for feeding a sheet to the image reading apparatus is provided. As an example of such a sheet feeding apparatus, there is proposed an automatic document feeding apparatus (ADF) for supplying a sheet of document to a document
10 reading portion.
15

 In such an ADF, a user is required to set documents on its document supporting stand with their leading edges being aligned when the documents are to be read.

20 However, when the documents are to be set with their leading edges being aligned, all the leading edges of the documents cannot be always aligned in the event that documents with different sizes are contained in a bundle of documents. In such cases, problems of jam, confused sheet feeding order, and
25 the like are likely to occur when the documents are separated and fed out one-by-one. Further, when

magnetic ink characters, such as MICR, are written on a document, the relative positional relationship between the reading portion and the magnetic ink character cannot be maintained under a preferable
5 condition if the aligning condition is inappropriate. Accordingly, the problem of inaccurate reading is liable to occur.

Therefore, the user is required to align the documents while confirming sizes of documents in the
10 bundle of documents to prevent the above-discussed problem. Such aligning operation of documents is, however, troublesome, and it is possible that the user will forget such aligning operation.

Conventionally, banks, for example, are
15 equipped with an aligning apparatus in which a bundle of checks, which exemplifies a bundle of sheets, is placed in an erect posture, and aligning and setting operation of the bundle of checks is performed by vibrating it.

20 Figs. 9 and 10 illustrate the construction of such an aligning apparatus. In Figs. 9 and 10, reference numeral 20 designates a main body of the apparatus including therein a vibrating unit (not shown). Reference numeral 23 designates a stand for
25 supporting a bundle of checks 13 thereon. Reference numeral 22 designates a connecting rod one end of which is connected to the vibrating unit of the

apparatus main body 20, and the other end of which is connected to the supporting stand 23. Reference numeral 21 designates an operation switch. Upon depressing the switch 21 after the checks 13 are put
5 on the supporting stand 23, the vibrating unit of the apparatus main body 20 vibrates the supporting stand 23 through the connecting rod 22.

When the supporting stand 23 vibrates in such a manner, the checks 13 are continuously hit against
10 alignment faces 24 and 25 of the supporting stand 23. The alignment face 24 is comprised of a wall face of the supporting stand 23, and serves to align the side face of the bundle of checks 13. The alignment face 25 is comprised of a bottom face of the supporting
15 stand 23, and serves to align the bottom face of the bundle of checks 13. The bundle of checks 13 is hence aligned with the alignment faces 24 and 25.

Accordingly, even when the bundle of checks 13 containing checks with different sizes is placed on
20 the supporting stand 23, aligning operation of the individual checks 13 with the alignment faces 24 and 25 can be preferably achieved. Further, air gaps can be generated between the checks during the check aligning operation, and hence the checks 13 can also
25 be loosened.

Therefore, if the sheet feeding apparatus is equipped with the above-discussed aligning apparatus,

documents can be assuredly aligned. When the user is to place the documents in such a sheet feeding apparatus, there is no need to align the individual papers and the productivity can be largely increased.

5 No sheet feeding apparatuses equipped with aligning apparatuses can be so far located, and no prior art documents in connection therewith can be hence found.

When such an aligning apparatus is to be provided in a sheet feeding apparatus, there are
10 fears that the document be badly fed in its paper feeding mechanism, and troubles occur in the event that vibration is excessive during the document aligning operation.

Accordingly, the sheet feeding apparatus needs
15 to be constructed such that its sufficient rigidity can be secured and adverse influences due to its vibrating motion can be prevented. However, when the sheet feeding apparatus is constructed in such a manner, its size and cost are likely to increase.

20

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a sheet aligning apparatus constructed without the above-discussed disadvantages.

25 It is another object of the present invention to provide a sheet aligning apparatus capable of assuredly aligning sheets without increasing its size

and cost, and a sheet feeding apparatus provided with such a sheet aligning apparatus.

These and further aspects and features of the invention will become apparent from the following
5 detailed description of preferred embodiments thereof in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a plan view viewed from the above
10 illustrating a document feeding apparatus of a first embodiment according to the present invention;

Fig. 2 is a cross-sectional side view of the document feeding apparatus;

Fig. 3 is a view illustrating a rotary member
15 provided in the document feeding apparatus;

Fig. 4 is a view illustrating another example of a rotary member which is in a standstill state;

Figs. 5A and 5B are views exemplifying shapes or profiles of rotary members, respectively;

20 Figs. 6A and 6B are views illustrating another constructions of aligning units, respectively;

Fig. 7 is a block diagram illustrating a control system of the document feeding apparatus;

Fig. 8 is a block diagram illustrating a
25 control system of a document feeding apparatus of a second embodiment according to the present invention;

Fig. 9 is a perspective view illustrating a

conventional aligning apparatus; and

Fig. 10 is a cross-sectional side view illustrating the conventional aligning apparatus.

5 DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will hereinafter be described with reference to the drawings. Sizes, materials, shapes or profiles, relative positional relationships, and so forth of
10 constituent components of those embodiments are not limited to those described therein, otherwise specific description thereof is made.

Fig. 1 is a plan view viewed from the above illustrating a document feeding apparatus, which
15 exemplifies a sheet feeding apparatus, provided in an image reading apparatus of a first embodiment according to the present invention, and Fig. 2 is its cross-sectional side view.

Further, Fig. 7 is a block diagram illustrating
20 a control system of the document feeding apparatus. In Fig. 7, reference numeral 100 designates an operation portion. Reference numeral 110 designates a control portion for controlling the document feeding apparatus. Reference numeral 120 designates
25 sensors including a sensor 7 described later. Reference numeral 130 designates motors for driving various movable members such as a pressure plate 3, a

shutter 4, and a sheet feeding roller 5 described later.

In Figs. 1 and 2, reference numeral 1 designates a document feeding apparatus provided in an image reading apparatus (not shown). Reference numeral 2 designates a document or sheet supporting stand on which documents 13 or sheets are placed in an erect or upstanding state. The document supporting stand 2 is provided with the pressure plate 3 for holding the documents 13 in an erect posture, and thrusting the documents 13 against an aligning wall 2A such that the documents 13 are not put in disorder.

The document supporting stand 2 is used in various ways. In one use situation, as many documents 13 as possible are put on the document supporting stand 2 so as to feed as many documents 13 as possible. In another situation, a very small amount of documents 13 far less than the document supporting capacity of the supporting stand 2 are put and handled on the document supporting stand 2.

Accordingly, to flexibly cope with those situations, the pressure plate 3 is urged toward the aligning wall 2A of the document supporting stand 2 by a biasing unit (not shown), and is movable within a range between positions indicated by the solid line and the alternate long and two short dashes line in

Fig. 1 in conformity with the amount of documents 13 when the documents 13 are put on the supporting stand 2. The pressure plate 3 is moved from a position for pushing the documents 13 to the position indicated by the alternate long and two short dashes line by a moving unit (not shown) when document aligning operation (described later) is to be started.

Reference numeral 5 designates a sheet feeding roller (sheet feeding unit) for feeding the documents 13 put on the document supporting stand 2. Reference numerals 51 and 52 respectively designate a feed roller and a retard roller for separating and feeding the documents 13 supplied from the feed roller 5 one by one to an image reading portion (not shown) located downstream of the feed roller 51 and the retard roller 52. Those feed roller and retard roller 51 and 52 constitute a separating and feeding portion. The feed roller 5 is disposed in such a manner that a portion thereof projects from the aligning wall 2A as illustrated in Fig. 1, and is supported movably upward and downward as illustrated in Fig. 2. Reference numeral 2B designates a document hitting portion against which the documents 13 are hit during the document aligning operation described later.

Reference numeral 4 designates a shutter provided at approximately the same place as the

document hitting portion 2B so as to be retractably disposed in a document conveyance path between the feed roller 5 and the separating and feeding portion. As illustrated in Fig. 2, the shutter 4 can be moved
5 from a position indicated by the alternate long and two short dashes line underneath a document supporting surface 2C of the supporting stand 2 to a position indicated by the solid line in which a leading edge of the document 13 hits against the
10 shutter 4, when the bundle of documents 13 is aligned as described later. The document 13 can be prevented from entering the separating and feeding portion by the thus-projected shutter 4 during the aligning operation.

15 When the document 13 is to be fed out after the aligning operation is completed, the shutter 4 is moved from the projecting position indicated by the solid line in Fig. 1 to the position underneath the document supporting surface 2C indicated by the
20 alternate long and two short dashes line in which the shutter 4 is retracted from the conveyance path so as not to interrupt the feed-out of the document 13.

Reference numerals 6a and 6b designate rotary members which constitute the aligning unit and rotate
25 in the sheet feeding direction to align ends of the documents 13. When the rotary members 6a and 6b rotate, portions thereof project from the document

supporting surface 2C. Due to such rotations of the rotary members 6a and 6b accompanied with intermittent projections of portions thereof from the document supporting surface 2C, the documents 13 put
5 on the document supporting surface 2C can be dropped after lifted, and the documents 13 can be moved toward the document hitting portion 2B to hit their leading edges against the document hitting portion 2B.

Leading edges and bottom edges of the documents
10 13 can be aligned due to such motion of the documents 13, i.e., the motion of the documents 13 in which they are continuously vibrated up and down for a predetermined time, and moved in the sheet feeding direction to hit against the hitting portion 2B by
15 the rotary members 6a and 6b.

Reference numerals 10a and 10b designate shafts of the two rotary members 6a and 6b, respectively, and reference numerals 8 and 9 designate pulleys fixed to these shafts 10a and 10b, respectively.
20 Those two pulleys 8 and 9 are coupled to each other through a belt 11. Rotation of one of the rotary members 6a and 6b rotated by a gear train (not shown) can be transmitted to the other rotary member through those pulleys 8 and 9, and the belt 11.

25 Projecting portions 12a and 12b formed in one pulley 9 are rotated together with rotation of the pulley 9, and interrupt light emitted in a sensor 7

of a light emission and reception type (a photo interrupter) each time the pulley 9 rotates a half rotation.

When the projecting portions 12a and 12b
5 rotating together with the pulley 9 block the light path of the sensor 7 of the light emission and reception type at a predetermined rotational period, the control apparatus 110 detects the rotational position of the rotary members 6a and 6b based on
10 electrical signals from the sensor 7 generated corresponding to the light blocking.

When the document feeding apparatus 1 is in its standby state, the rotary members 6a and 6b do not project from the document supporting surface 2C as
15 illustrated in Fig. 2, and remain stationary in their standby positions retracted under the document supporting surface 2C. At this moment, one of the projecting portions 12a and 12b interrupts the light path in the sensor 7 of the photo interrupter type.
20 The control apparatus can thus recognize that the rotary members 6a and 6b are in their standby positions.

In the thus-constructed document feeding apparatus 1, upon depressing the operation switch of
25 the operation portion 100, aligning operation of aligning ends of the documents is initially performed, and thereafter the plural end-aligned documents are

separated and fed out one by one, and supplied to the image reading portion (not shown).

Description will now be made of those aligning operation of aligning ends of the documents and
5 document feeding operation.

When the user places a plurality of sheets of documents 13 on the supporting stand 2 and depresses the operation switch of the operation portion 100, the pressure plate 3 is initially retracted from the
10 position indicated by the solid line in Fig. 1 to the position indicated by the alternate long and two short dashes line in Fig. 1 by the moving unit (not shown) such that pressing force against the bundle of documents 13 can be weakened, i.e., such that the
15 aligning operation by the rotary members 6a and 6b cannot be prevented. Further, the shutter 4 is projected to the position indicated by the solid line in Fig. 1 to close the conveyance path of the documents 13.

20 The pressure plate 3 is retracted as discussed above, and the rotary members 6a and 6b start to be rotated through the gear train (not shown), the two pulleys 8 and 9, and the belt 11. When the rotary members 6a and 6b are thus rotated, four curved
25 corner portions 60 to 63, which are portions of the rotary members 6a and 6b, successively project from the document supporting surface 2C to lift the bottom

edge of the bundle of documents 13, and then retract as illustrated in Fig. 3.

For example, when the first corner portion 60 projects from the document supporting stand 2, the rotary members 6a and 6b come into contact with the documents 13 at a point P0 while rotating. After that, the bundle of documents 13 is lifted perpendicularly to the document supporting stand 2 by the rotary members 6a and 6b during the rotation of the rotary members 6a and 6b, and is conveyed downstream of the horizontal conveyance path in the sheet feeding direction by friction force between the rotary members 6a and 6b and the bundle of documents 13. Afterward, when the rotary members 6a and 6b retract downward underneath the document supporting stand 2, the bundle of documents 13 falls down to the document supporting surface 2C due to the gravity, and is brought to a state moved downstream of the conveyance path.

When the second corner portion 61 located upstream of the first corner portion 60 in the rotational direction then comes into contact with the documents 13 at a point P1 during the rotation of the rotary members 6a and 6b, the bundle of documents 13 is lifted from the document supporting stand 2 following the rotation of the rotary members 6a and 6b similar to the case of the first corner portion 60.

Then, when the rotary members 6a and 6b retract downward underneath the document supporting stand 2, the bundle of documents 13 falls down to the document supporting surface 2C, and is brought to a state
5 moved downstream of the conveyance path.

The bundle of documents 13 is thus moved downstream of the conveyance path until its leading edge hits against the hitting portion 2B by the rotation of the rotary members 6a and 6b.

10 When the bundle of documents 13 thus reaches the hitting portion 2B and the shutter 4 due to the rotation of the rotary members 6a and 6b, there can occur a case where a document with a smaller size in the bundle of documents 13 does not yet reach the
15 hitting portion 2B and the shutter 4, for example. Even in such a case, however, the document with a smaller size can be gradually conveyed downstream of the conveyance path toward the hitting portion 2B and the shutter 4 by the above-discussed operation to be
20 successively executed afterward.

The documents having already arrived at the hitting portion 2B and the shutter 4 repeat the following motion while being prevented from moving forward by the hitting portion 2B and the shutter 4.
25 In such motion, after lifted above the document supporting surface 2C by the motion of the rotary members 6a and 6b, the documents are dropped again.

The bundle of documents 13 can be sufficiently aligned with the document supporting surface 2C by the above-discussed repetitive vibrations (lifting and dropping) of the bundle of documents 13. At the
5 same time, sticking force generated between the documents is eliminated, and air gaps are created between the documents. The documents can be thereby loosened. The following separating and feeding operation of the documents can be smoothly achieved
10 due to the effect of such loosening operation. Further, even when documents with different sizes are contained in the bundle of documents 13, leading edges of the individual documents 13 can be aligned due to continuous hitting motion of the bundle of
15 documents 13 against the hitting portion 2B and the shutter 4.

Afterward, the rotary members 6a and 6b are rotated for such a period that all the documents are sufficiently aligned with the document hitting
20 portion 2B, the shutter 4, and the document supporting surface 2C, and the documents repeat the above-discussed motion for a predetermined period. Then, the control apparatus controls the rotary members 6a and 6b to stay in the standby positions
25 which are detected by the above-mentioned sensor 7 of the photo interrupter type.

For example, the control apparatus counts the

number of interruptions of the optical path in the sensor 7 by the protruding portions 12a and 12b of one pulley 9, and stops the rotation of the rotary members 6a and 6b when the counted value reaches a
5 predetermined value. At the same time, the control apparatus retracts the shutter 4 from the document supporting stand 2 back to the position indicated by the alternate long and two short dashes line in Fig. 1. The operation for aligning the ends of the
10 documents is thus finished. At this moment, the rotary members 6a and 6b are stopped at positions retracted from the document supporting surface 2C as illustrated in Fig. 2.

After completion of the above-discussed
15 aligning operation of aligning ends of the documents, the bundle of documents 13 is fed out by the feed roller 5 as discussed above. Afterward, the documents are separated and conveyed one by one by the feed roller 51 and the retard roller 52. All the
20 operations are completed after all the documents are fed out from the document supporting stand 2.

As described in the foregoing, after the bundle of documents 13 is placed in an erect posture on the document supporting stand 2, the bundle of documents
25 13 is continuously vibrated up and down for a predetermined time, and is moved in the sheet feeding direction by the rotary members 6a and 6b. The

bundle of documents 13 is hence hit against the document hitting portion 2B and the shutter 4. The ends of the bundle of documents 13 can be thus aligned by a simple structure.

5 Further, size, weight, and space of the document feeding apparatus or sheet supplying apparatus can be reduced, and the apparatus can be produced at relatively low costs.

 In the above-discussed structure, the standby
10 state is established when the two rotary members 6a and 6b are retracted from the document supporting stand 2. However, it is possible to establish the standby state when portions (corner portions) of the rotary members 6a and 6b are projected from the
15 document supporting stand 2 as illustrated in Fig. 4. In such a construction, projecting portions 12a and 12b are formed in one rotary member 6b such that either of projecting portions 12a and 12b can interrupt the optical path in the sensor 7 of the
20 photo interrupter type when the rotary member 6b stays in the standby state illustrated in Fig. 4.

 In such a structure where the standby state is established when the two rotary members 6a and 6b project by the same height from the document
25 supporting stand 2, but not when the two rotary members 6a and 6b are retracted from the document supporting stand 2, the bundle of documents 13 can be

kept in such a posture that does not adversely
influence subsequent feeding operation even if the
document supporting surface 2C has an uneven portion.
Further, the bundle of documents 13 can be kept under
5 a more appropriate condition by finely adjusting the
amount of the above projection.

The two rotary members 6a and 6b are projected
by the same height in the above structure to maintain
the bundle of documents in such a posture that does
10 not adversely influence the feeding operation, but
the structure is not limited thereto. For example,
in the event that the document supporting surface 2C
is sloped, it is possible to establish the standby
state when the two rotary members 6a and 6b project
15 by different heights from the document supporting
stand 2, and keep the bundle of documents 13 under a
slant condition relative to the document supporting
surface 2C.

Furthermore, in the above-discussed structure,
20 square-shaped rotary members 6a and 6b with four
corners are used as the aligning unit that repeats
projection and retraction from the document
supporting surface 2C, but the rotary member is not
limited thereto. The shape or profile of the rotary
25 member 6 can be an eccentric cylinder as illustrated
in Fig. 5A, or a cam shape as illustrated in Fig. 5B.
The above-discussed appropriate height position and

slope direction of the bundle of documents can be finely set by using the rotary members with those shapes.

Further, the aligning unit is not limited to
5 the above-discussed rotary member 6. The following aligning unit can also be used. One example includes a cam member 6A and a vibrating member 6B as illustrated in Fig. 6A, and the vibrating member 6B is adapted to repeat projection and retraction from
10 the document supporting surface 2C according to the profile of the cam member 6A. Another example includes a cam member 6A and a vibrating member 6C as illustrated in Fig. 6B, and the vibrating member 6C is adapted to repeat slant-moving projection and
15 retraction from the document supporting surface 2C according to the profile of the cam member 6A.

In the structure illustrated in Fig. 6A, phases of the cam members 6A can be made different from each other such that the vibrating member 6B can move up
20 and down in a slant posture so as to guide the bundle of documents 13 toward the shutter 4 as indicated by the arrow.

When the up and down movement of the vibrating members 6B and 6C is effected by the above-discussed
25 cam member 6A, it is possible to preferably achieve the aligning operation of aligning ends of the bundle of documents 13 by moderate vibration. Such

structures are effective particularly when the document is thin, and is hence likely to bend.

The aligning operation of aligning edges of the documents can be more effectively executed when the user can appropriately set at least one of operation
5 conditions, such as operation time of the aligning operation, the number of projection and retraction movements of the rotary member 6 and the vibrating members 6B and 6C (the number of vibrations of the
10 bundle of documents 13), speed thereof, and an amplitude of the up and down vibration of the bundle of documents 13, in conformity with conditions such as the amount of the bundle of documents 13, and quality of paper.

15 Further, when the amount of the bundle of documents 13 is detected by a sensor or the like such that operation conditions can be automatically set in conformity with the detected amount, the user need not make troublesome selection of appropriate
20 operation conditions according to the amount of the bundle of documents 13. Operability of the apparatus can be hence remarkably improved.

Fig. 8 is a block diagram illustrating a control system in a sheet feeding apparatus of a
25 second embodiment of the present invention, in which operation conditions can be automatically set in conformity with the amount of the bundle of documents

13. In Fig. 8, reference numeral 14 designates an operation condition setting portion by which the user can appropriately set operation conditions, such as operation time of the aligning operation, the number
5 of projection and retraction movements of the rotary member and the vibrating member, and speed thereof, in conformity with conditions such as the amount of the bundle of documents 13, and quality of paper. Reference numeral 16 designates an operation
10 condition storing portion for storing the operation conditions appropriately set by the user. Reference numeral 15 designates a CPU, and reference numeral 17 designates an aligning portion described using Figs. 1 to 7 in the foregoing.

15 The CPU 15 serves to cause the operation condition storing portion 16 to hold information set by the operation condition setting portion 14, and also serves to supply electrical signals of the stored operation conditions to the aligning portion
20 17 when the aligning operation is to be performed, and cause the aligning portion 17 to perform the operation of aligning ends of the documents (the aligning operation). The operation condition storing portion 16 thus holds the once-set operation
25 conditions, and therefore there is no need to newly set the conditions since the stored set conditions can be called for subsequent operation.

Further, in Fig. 8, reference numeral 18 designates a document stacking amount detecting portion that is a detecting unit for detecting the amount of the documents 13 placed on the document supporting stand 2. The CPU 15 acting as a changing unit can change at least one of the above-discussed operation conditions in conformity with the detected amount.

The document stacking amount detecting portion 18 has a structure in which the amount of the documents 13 is detected by detecting a held position of the pressure plate 3 as illustrated in Fig. 1, for example. The CPU 15 can recognize the amount of the documents based on an electrical signal corresponding to such held position.

In such a construction, the CPU 15 can automatically set at least one of the above operation conditions in conformity with the detected amount of the documents 13, and accordingly the user need not make troublesome selection of appropriate operation conditions according to the amount of the bundle of documents 13. Operability of the apparatus can be hence remarkably improved.

In the above-discussed operation setting, the operation of aligning edges of the documents, and the document feeding operation are sequentially performed automatically. The present invention, however, is

not limited thereto. It is also possible to perform only the document feeding operation unless the user desires to execute the aligning operation, or perform only the aligning operation. Such selection can be
5 appropriately made, and is stored in the operation condition storing unit 16 from the operation condition setting portion 14 through the CPU 15.

In the construction where the aligning operation can be thus selectively performed, the
10 document feeding operation can be directly executed when there is no need to align the documents, for example, when documents with the same size are put on the supporting stand. Further, when the user desires to align the bundle of documents beforehand
15 prior to storage, conveyance or transportation of the documents, it is possible to perform only the aligning operation. Efficiency can be hence increased.

While the present invention has been described
20 with reference to what are presently considered to be the preferred embodiments, it is to be understood that the invention is not limited to the disclosed embodiments. On the contrary, the invention is intended to cover various modifications and
25 equivalent arrangements included within the spirit and scope of the appended claims. The scope of the following claims is to be accorded the broadest

interpretation so as to encompass all such
modifications and equivalent structures and functions.